

SPECIFICATION SHEET

5 1/2" OD, DSTJ, 7" X 3 1/2" TJ, HEAVY WEIGHT - CONVENTIONAL

PIPE OD	5 1/2"
ADJUSTED WEIGHT	55.62 LBS/FT
AVERAGE WEIGHT (TOTAL LENGTH)	1,705 LBS/JT
AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	1.000"
AVERAGE INSIDE DIAMETER (NEW)	3.500"
PIPE COLLAPSE RESISTANCE (NEW)	32,727 PSI
PIPE INTERNAL YIELD PRESSURE (NEW)	35,000 PSI
PIPE TENSILE YIELD (NEW)	1,555,100 LBS
PIPE TORSIONAL YIELD (NEW)	144,400 FT-LBS
CONNECTION	5 1/2" FH DSTJ
PIN / BOX OD	7.000"
PIN / BOX ID	3.500"
HARDBANDING	ARMACOR 'M'
TOOL JOINT TENSILE YIELD (NEW)	1,484,300 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	85,200 LBS-FT
PIN / BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	30,100 FT-LBS
MAKE UP TORQUE (MAXIMUM)	44,900 FT-LBS
FLUID DISPLACEMENT	0.840 GAL/FT
FLUID CAPACITY	0.500 GAL/FT
DRIFT SIZE	3.375"

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 44,900 ft-lbs

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Mohammad Khan	Date: 16/11/09	Approved by: Colin Cooper	Date: 23/11/09	Approved by: Rob O'Neill	Date: 30/11/09
------------------------------	-------------------	------------------------------	-------------------	-----------------------------	-------------------