

SPECIFICATION SHEET

3 1/8" OD, HTPAC, 3 1/8" X 1 1/4" TJ DRILL COLLAR

| | |
|----------------------------------|--------------|
| TUBE O.D. | 3 1/8" |
| TUBE I.D. | 1 1/4" |
| CONNECTION | HTPAC |
| AVERAGE WEIGHT | 678 LBS |
| APPROXIMATE LENGTH | 31 FT |
| ADJUSTED WEIGHT | 21.88 LBS/FT |
| TOOL JOINT O.D. | 3 1/8" |
| TOOL JOINT I.D. | 1 1/4" |
| HARDBANDING | NONE |
| TOOL JOINT TENSILE YIELD (NEW) | 309,700 LBS |
| TOOL JOINT TORSIONAL YIELD (NEW) | 9,400 FT-LBS |
| MAKE UP TORQUE (MINIMUM) | 3,500 FT-LBS |
| MAKE UP TORQUE (MAXIMUM) | 5,600 FT-LBS |
| FLUID DISPLACEMENT | 0.335 GAL/FT |
| FLUID CAPACITY | 0.064 GAL/FT |
| DRIFT SIZE | 1.125" |
| BSR | 2.146 |

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

| | | | | | |
|------------------------------|-------------------|------------------------------|-------------------|-------------------------------|-------------------|
| Originator: Doug Farquhar | Date: 30/07/07 | Approved by: Colin Cooper | Date: 06/08/07 | Approved by: Darren Mourre | Date: 10/08/07 |
|------------------------------|-------------------|------------------------------|-------------------|-------------------------------|-------------------|