

SPECIFICATION SHEET

3 3/8" OD, WT26, 3 3/8" X 1 3/4" TJ, DRILL COLLAR

TUBE O.D.	3 3/8"
TUBE I.D.	1 3/4"
CONNECTION	WT26
AVERAGE WEIGHT	688 LBS
APPROXIMATE LENGTH	31 FT
ADJUSTED WEIGHT	22.2 LBS/FT
TOOL JOINT O.D.	3 3/8"
TOOL JOINT I.D.	1 3/4"
HARDBANDING	NONE
TOOL JOINT TENSILE YIELD (NEW)	416,000 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	13,200 FT-LBS
MAKE UP TORQUE (MINIMUM)	2,800 FT-LBS
MAKE UP TORQUE (MAXIMUM)	9,800 FT-LBS
FLUID DISPLACEMENT	0.307 GAL/FT
FLUID CAPACITY	0.185 GAL/FT
DRIFT SIZE	1.625"

Note 1: Make up torque should always be higher than anticipated drilling torque – up to a maximum of 9,800 ft-lbs.

Note 2: Connections do **NOT** shoulder out. There should be a gap when made up to recommended max torque.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 30/07/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------