

SPECIFICATION SHEET

4 3/4" OD, PH6, TUBING TEST DRILL COLLAR

TUBE O.D.	4 3/4"
TUBE I.D.	2 1/4"
CONNECTION	3 1/2" PH6, 12.95 LB/FT
AVERAGE WEIGHT	1,349 LBS
APPROXIMATE LENGTH	31 FT
ADJUSTED WEIGHT	43.5 LBS/FT
TOOL JOINT O.D.	4.313"
TOOL JOINT I.D.	2.687"
HARDBANDING	NONE
TOOL JOINT TENSILE YIELD (NEW)	405,000 LBS
MAKE UP TORQUE (MINIMUM)	7,000 FT-LBS
MAKE UP TORQUE (MAXIMUM)	8,800 FT-LBS
FLUID DISPLACEMENT	0.714 GAL/FT
FLUID CAPACITY	0.207 GAL/FT
DRIFT SIZE	2.125"

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum 8,800 ft-lbs

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Mohammad Khan	Date: 11/02/09	Approved by: Colin Cooper	Date: 12/02/09	Approved by: Rob O' Neill	Date: 12/02/09
------------------------------	-------------------	------------------------------	-------------------	------------------------------	-------------------