

SPECIFICATION SHEET

8" OD, 6 5/8" REG, 8.000" X 2.813" TJ, DRILL COLLAR

TUBE O.D.	8"
TUBE I.D.	2 13/16"
CONNECTION	6 5/8" REG
AVERAGE WEIGHT	4,638 LBS
APPROXIMATE LENGTH	31 FT
ADJUSTED WEIGHT	149.60 LBS/FT
TOOL JOINT O.D.	8"
TOOL JOINT I.D.	2 13/16"
HARDBANDING	ARMACOR M
TOOL JOINT TENSILE YIELD (NEW)	1,834,500 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	85,500 FT-LBS
MAKE UP TORQUE (MINIMUM)	53,500 FT-LBS
MAKE UP TORQUE (MAXIMUM)	59,000 FT-LBS
FLUID DISPLACEMENT	2.288 GAL/FT
FLUID CAPACITY	0.323 GAL/FT
DRIFT SIZE	2.688"
BSR	2.60

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 59,000 ft-lbs.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 30/07/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------