

## SPECIFICATION SHEET

9 1/2" OD, 7 5/8" REG, 9.500" X 3.000" TJ, DRILL COLLAR

TUBE O.D.	9 1/2"
TUBE I.D.	3"
CONNECTION	7 5/8" REG
AVERAGE WEIGHT	6,718 LBS
APPROXIMATE LENGTH	31.50 FT
ADJUSTED WEIGHT	216.71 LBS/FT
TOOL JOINT O.D.	9.500"
TOOL JOINT I.D.	3.000"
HARDBANDING	ARMACOR M & NONE
TOOL JOINT TENSILE YIELD (NEW)	2,661,800 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	141,900 FT-LBS
MAKE UP TORQUE (MINIMUM)	88,500 FT-LBS
MAKE UP TORQUE (MAXIMUM)	97,500 FT-LBS
FLUID DISPLACEMENT	3.315 GAL/FT
FLUID CAPACITY	0.367 GAL/FT
DRIFT SIZE	2.875"
BSR	2.815

**Note:** Make up torque should always be higher than anticipated drilling torque – to a maximum of 97,500 ft-lbs.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 30/07/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------