

SPECIFICATION SHEET

4" OD, 14.00 LBS/FT, HT40, 5.000" X 2.688" TJ, S-135 DRILL PIPE

PIPE SPECIFICATION	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE OD	4.000"	<p>Note 1: The operating limits of the drill pipe should be based on the Premium pipe data detailed below.</p> <p>Any technical queries should be directed to Premier's Engineering Department</p>
NOMINAL WEIGHT (PIPE TUBE)	14.00 LBS/FT	
AVERAGE WEIGHT (TUBE & TJ)	492 LBS	
AVERAGE LENGTH	31.50 FT	
ADJUSTED WEIGHT	15.60 LBS/FT	
NOMINAL WALL THICKNESS	0.330"	
AVERAGE INSIDE DIAMETER	3.340"	
TYPE OF UPSET	IU	
GRADE	S-135	
INTERNAL PLASTIC COATING	TK 34 XT	
PIPE CAPACITIES	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE TENSILE YIELD	513,600 LBS	403,500 LBS
PIPE TORSIONAL YIELD	41,900 FT-LBS	32,800 FT-LBS
PIPE COLLAPSE RESISTANCE	20,141 PSI	13,836 PSI
PIPE BURST RESISTANCE	19,491 PSI	17,820 PSI
TOOL JOINT SPECIFICATION		
CONNECTION	HT40	<p>Note 2: Make up torque should always be higher than anticipated drilling torque – up to a maximum of 17,600 ft/lbs.</p>
PIN / BOX OD	5.000"	
PIN / BOX ID	2.688"	
HARDBANDING	ARMACOR M	
TOOL JOINT TENSILE YIELD	776,400 LBS	
TOOL JOINT TORSIONAL YIELD	29,400 FT-LBS	
PIN / BOX LENGTH	9" / 15"	
MAKE UP TORQUE (MINIMUM)	11,600 FT-LBS	
MAKE UP TORQUE (MAXIMUM)	17,600 FT-LBS	
FLUID DISPLACEMENT	0.239 GAL/FT	
FLUID CAPACITY	0.439 GAL/FT	
DRIFT SIZE	2.563"	

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 27/03/08	Approved by: Colin Cooper	Date: 28/03/08	Approved by: Rob O'Neil	Date: 11/04/08
------------------------------	-------------------	------------------------------	-------------------	----------------------------	-------------------