

SPECIFICATION SHEET

5 1/2" OD, 21.90 LBS/FT, TT550, 6.625" X 4.250" TJ, TSS-105 DRILL PIPE

PIPE SPECIFICATION	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE OD	5.500"	<p>Note 1: The operating limits of the drill pipe should be based on the Premium pipe data detailed below.</p> <p>Any technical queries should be directed to Premier's Engineering Department</p>
NOMINAL WEIGHT (PIPE TUBE)	21.90 LBS/FT	
AVERAGE WEIGHT (TUBE & TJ)	764 LBS	
AVERAGE LENGTH	31.50 FT	
ADJUSTED WEIGHT	24.24 LBS/FT	
NOMINAL WALL THICKNESS	0.361"	
AVERAGE INSIDE DIAMETER	4.778"	
TYPE OF UPSET	IEU	
GRADE	TSS-105	
INTERNAL PLASTIC COATING	TK 34 XT	
PIPE CAPACITIES	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE TENSILE YIELD	612,000 LBS	482,700 LBS
PIPE TORSIONAL YIELD	71,000 FT-LBS	55,800 FT-LBS
PIPE COLLAPSE RESISTANCE	10,753 PSI	6,865 PSI
PIPE BURST RESISTANCE	12,061 PSI	11,027 PSI
TOOL JOINT SPECIFICATION		
CONNECTION	TT550	<p>Note 2: Make up torque should always be higher than anticipated drilling torque – up to a maximum of 46,900 ft/lbs.</p>
PIN / BOX OD	6.625"	
PIN / BOX ID	4.250"	
HARDBANDING	TCS TI	
TOOL JOINT TENSILE YIELD	966,200 LBS	
TOOL JOINT TORSIONAL YIELD	78,200 FT-LBS	
PIN / BOX LENGTH	12" / 17"	
MAKE UP TORQUE (MINIMUM)	39,100 FT-LBS	
MAKE UP TORQUE (MAXIMUM)	46,900 FT-LBS	
FLUID DISPLACEMENT	0.370 GAL/FT	
FLUID CAPACITY	0.908 GAL/FT	
DRIFT SIZE	4.125"	

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Mohammad Khan	Date: 04/02/09	Approved by: Colin Cooper	Date: 05/02/09	Approved by: Rob O Neill	Date: 05/02/09
------------------------------	-------------------	------------------------------	-------------------	-----------------------------	-------------------