

SPECIFICATION SHEET

5 7/8" OD, (0.500" WALL), CT-M57, 7.000" X 4.250" TJ, S-135 DRILL PIPE

PIPE SPECIFICATION	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE OD	5.875"	<p>Note 1: The operating limits of the drill pipe should be based on the Premium pipe data detailed below.</p> <p>Any technical queries should be directed to Premier's Engineering Department.</p>
NOMINAL WEIGHT (PIPE TUBE)	30.20 LBS/FT	
AVERAGE WEIGHT (TUBE & TJ)	1,057 LBS	
AVERAGE LENGTH	31.50 FT	
ADJUSTED WEIGHT	33.55 LBS/FT	
NOMINAL WALL THICKNESS	0.500"	
AVERAGE INSIDE DIAMETER	4.875"	
TYPE OF UPSET	IEU	
GRADE	S-135	
INTERNAL PLASTIC COATING	TK 34 XT	
PIPE CAPACITIES	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE TENSILE YIELD	1,359,800 LBS	894,900 LBS
PIPE TORSIONAL YIELD	135,900 FT-LBS	106,100 FT-LBS
PIPE COLLAPSE RESISTANCE	21,023 PSI	14,824 PSI
PIPE BURST RESISTANCE	20,106 PSI	19,031 PSI
TOOL JOINT SPECIFICATION		
CONNECTION	CT-M57	<p>Note 2: Connections should be made up to maximum make up torque value to ensure the integrity of the gas tight seal.</p>
PIN / BOX OD	7.000"	
PIN / BOX ID	4.250"	
HARDBANDING	ARMACOR M	
TOOL JOINT TENSILE YIELD	1,359,800 LBS	
TOOL JOINT TORSIONAL YIELD	96,700 FT-LBS	
PIN / BOX LENGTH	12"/17"	
MAKE UP TORQUE (MINIMUM)	43,000 FT-LBS	
MAKE UP TORQUE (MAXIMUM)	51,600 FT-LBS	
FLUID DISPLACEMENT	0.513 GAL/FT	
FLUID CAPACITY	0.951 GAL/FT	
DRIFT SIZE	4.125"	

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 17/07/07	Approved by: Colin Cooper	Date: 01/08/07	Approved by: Darren Mourre	Date: 10/08/08
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------