

STABILIZER SPECIFICATIONS

Hole Size (in)	Body Size (Dia. in)	Bore (Dia. in)	Overall (Length in)	Approx. Weight (lbs)	Connection
5 5/8 5 7/8 6	4 1/8	2	60	280	NC38
6 1/8 6 1/4 6 1/2 6 5/8 6 3/4	4 3/4	2 or 2 1/4	60	370	NC38
7 3/8 7 5/8 7 7/8	6 1/4	2 1/4	72	560	NC50
8 3/8 8 1/2 8 5/8 8 3/4	6 1/4 or 6 3/4	2 1/4 or 2 1/2	84	720	NC50
9 9 1/2 9 5/8	6 3/4	2 1/4	87	1100	NC50
9 7/8	7 3/4	2 1/2	87	1100	6 5/8" REG
10 5/8 11 12	8	2 13/16	95	1400	6 5/8" REG
12 1/4	8	3	95	2050	6 5/8" REG
13 1/2 14 3/4	8 or 9 1/2	2 13/16	101	2200	6 5/8" REG or 7 5/8" REG
16 1/2 17 1/2 18 1/8	9 1/2	3	103	2700	7 5/8" REG
20 22 24 26	9 1/2	3	120	4600	7 5/8" REG

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.