

SPECIFICATION SHEET

5 7/8" OD, (0.750" WALL), XT57, 7.000" X 3.500" TJ, S-135 LANDING STRING

PIPE SPECIFICATION	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE OD	5.875"	<p>Note 1: The operating limits of the drill pipe should be based on the Premium pipe data detailed below.</p> <p>Any technical queries should be directed to Premier's Engineering Department</p>
AVERAGE WEIGHT (TUBE & TJ)	1,455 LBS	
AVERAGE LENGTH	31.50 FT	
ADJUSTED WEIGHT	46.18 LBS/FT	
NOMINAL WALL THICKNESS	0.750"	
AVERAGE INSIDE DIAMETER	4.375"	
TYPE OF UPSET	IEU	
GRADE	S-135	
INTERNAL PLASTIC COATING	TK 100	
PIPE CAPACITIES	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE TENSILE YIELD	1,630,200 LBS	1,266,000 LBS
PIPE TORSIONAL YIELD	179,000 LBS	137,000 LBS
PIPE COLLAPSE RESISTANCE	30,068 PSI	25,931 PSI
PIPE BURST RESISTANCE	30,160 PSI	29,058 PSI
TOOL JOINT SPECIFICATION		
CONNECTION	XT57	
PIN / BOX OD	7.000"	
PIN / BOX ID	3.500"	
HARDBANDING	ARMACOR M	
TOOL JOINT TENSILE YIELD	1,756,500 LBS	
TOOL JOINT TORSIONAL YIELD	119,400 FT-LBS	
PIN / BOX LENGTH	12"/17"	
MAKE UP TORQUE (MINIMUM)	36,400 FT-LBS	
MAKE UP TORQUE (MAXIMUM)	71,600 FT-LBS	
FLUID DISPLACEMENT	0.706 GAL/FT	
FLUID CAPACITY	0.758 GAL/FT	
DRIFT SIZE	3.375"	

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 01/08/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------