

SPECIFICATION SHEET

5" OD, 25.60 LBS/FT, NC50, 6.625" X 2.750" TJ, V-150 LANDING STRING

PIPE SPECIFICATION	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE OD	5"	<p>Note 1: The operating limits of the drill pipe should be based on the Premium pipe data detailed below.</p> <p>Any technical queries should be directed to Premier's Engineering Department</p>
NOMINAL WEIGHT (PIPE TUBE)	25.60 LBS/FT	
AVERAGE WEIGHT (TUBE & TJ)	911 LBS	
AVERAGE LENGTH	31.50 FT	
ADJUSTED WEIGHT	28.93 LBS/FT	
NOMINAL WALL THICKNESS	0.500"	
AVERAGE INSIDE DIAMETER	4.000"	
TYPE OF UPSET	IEU	
GRADE	V-150	
INTERNAL PLASTIC COATING	TK 34 XT	
PIPE CAPACITIES	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE TENSILE YIELD	1,060,300 LBS	829,400 LBS
PIPE TORSIONAL YIELD	104,500 FT-LBS	81,100 FT-LBS
PIPE COLLAPSE RESISTANCE	27,000 PSI	22,329 PSI
PIPE BURST RESISTANCE	26,250 PSI	24,000 PSI
TOOL JOINT SPECIFICATION		
CONNECTION	NC50	
PIN / BOX OD	6.625"	
PIN / BOX ID	2.750"	
HARDBANDING	TCS TI	
TOOL JOINT TENSILE YIELD	1,551,700 LBS	
TOOL JOINT TORSIONAL YIELD	63,500 FT-LBS	
PIN / BOX LENGTH	9"/12"	
MAKE UP TORQUE (MINIMUM)	31,700 FT-LBS	
MAKE UP TORQUE (MAXIMUM)	32,900 FT-LBS	
FLUID DISPLACEMENT	0.443 GAL/FT	
FLUID CAPACITY	0.624 GAL/FT	
DRIFT SIZE	2.625"	

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 28/03/2008	Approved by: Colin Cooper	Date: 28/03/2008	Approved by: Rob O'Neill	Date: 28/03/2008
------------------------------	---------------------	------------------------------	---------------------	-----------------------------	---------------------