

SPECIFICATION SHEET

6 5/8" OD, 47.00 LBS/FT, FH, 8.500" X 4.250" TJ, S-135 LANDING STRING

PIPE SPECIFICATION	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE OD	6.625"	<p>Note 1: The operating limits of the drill pipe should be based on the Premium pipe data detailed below.</p> <p>Any technical queries should be directed to Premier's Engineering Department</p>
AVERAGE WEIGHT (TUBE & TJ)	1,718 LBS	
AVERAGE LENGTH	31.50 FT	
ADJUSTED WEIGHT	54.54 LBS/FT	
NOMINAL WALL THICKNESS	0.750"	
AVERAGE INSIDE DIAMETER	5.125"	
TYPE OF UPSET	IEU	
GRADE	S-135	
INTERNAL PLASTIC COATING	TK 34XT	
PIPE CAPACITIES	NEW	PREMIUM 80% REMAINING BODY WALL
PIPE TENSILE YIELD	1,868,800 LBS	1,456,800 LBS
PIPE TORSIONAL YIELD	237,900 FT-LBS	183,500 FT-LBS
PIPE COLLAPSE RESISTANCE	27,106 PSI	23,183 PSI
PIPE BURST RESISTANCE	26,745 PSI	25,613 PSI
TOOL JOINT SPECIFICATION		
CONNECTION	FH	
PIN / BOX OD	8.500"	
PIN / BOX ID	4.250"	
HARDBANDING	ARMACOR M	
TOOL JOINT TENSILE YIELD	2,102,300 LBS	
TOOL JOINT TORSIONAL YIELD	109,200 FT-LBS	
PIN / BOX LENGTH	10"/13"	
MAKE UP TORQUE (MINIMUM)	54,500 FT-LBS	
MAKE UP TORQUE (MAXIMUM)	56,000 FT-LBS	
FLUID DISPLACEMENT	0.834 GAL/FT	
FLUID CAPACITY	1.048 GAL/FT	
DRIFT SIZE	4.125"	

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 01/08/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------