

## SPECIFICATION SHEET

### 2 3/8" N80, 4.70 LBS/FT, EUE TUBING

PIPE OD / ID	2 3/8" / 1.995"
PIPE WEIGHT	4.70 LBS/FT
AVERAGE JOINT WEIGHT	146 LBS
AVERAGE JOINT LENGTH	31 FT
PIPE GRADE	N80
WALL	0.190"
DRIFT	1.901" MIN
PIPE CONNECTION	EUE
BOX COUPLING OD	3.000"
UPSET OD	2 19/32"
NEW PIPE TENSILE (YIELD)	104,000 LBS
NEW PIPE TORSIONAL	5,100 FT-LBS
NEW PIPE BURST	11,200 PSI
NEW PIPE COLLAPSE	11,780 PSI
CONNECTION YIELD	EXCEEDS PIPE
CAPACITY	0.00387 BBL/FT
DISPLACEMENT	0.00171 BBL/FT
CONNECTION PRESSURE RATING, BURST	AS PER NEW PIPE
CONNECTION PRESSURE RATING, COLLAPSE	AS PER NEW PIPE
CONNECTION MAKE-UP MINIMUM	1,350 FT-LBS
CONNECTION MAKE-UP OPTIMUM	1,800 FT-LBS
CONNECTION MAKE-UP MAXIMUM	2,250 FT-LBS

**Note:** All used figures have **NO** safety factor included for tension, temperature, or general S.F. etc.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 31/07/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------