

SPECIFICATION SHEET

2 3/8" AC95, 7.70 LBS/FT HYDRIL PH6 TUBING

PIPE OD / ID	2 3/8" / 1.703"
PIPE WEIGHT	7.70 LBS/FT
AVERAGE JOINT WEIGHT	239 LBS
AVERAGE JOINT LENGTH	31 FT
PIPE GRADE	AC95
WALL	0.336"
DRIFT	1.609" MIN
PIPE CONNECTION	PH6
BOX OD	3 3/32"
UPSET OD	3 3/32"
NEW PIPE TENSILE (YIELD)	200,000 LBS
NEW PIPE TORSIONAL	8,840 FT-LBS
NEW PIPE BURST	15,960 PSI
NEW PIPE COLLAPSE	16,490 PSI
CONNECTION YIELD	EXCEEDS TUBE
CONNECTION PRESSURE RATING, BURST	AS PER NEW PIPE
CONNECTION PRESSURE RATING, COLLAPSE	AS PER NEW PIPE
CONNECTION MAKE-UP MINIMUM	2,500 FT-LBS
CONNECTION MAKE-UP MAXIMUM	3,100 FT-LBS

Note: All used figures have **NO** safety factor included for tension, temperature, or general S.F. etc.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 31/07/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------