

SPECIFICATION SHEET

2-7/8" N-80, 6.4 LBS/FT, HYDRIL 511 TUBING

PIPE OD / ID	2.875" / 2.441"
PIPE WEIGHT	6.40 LBS/FT
AVERAGE JOINT WEIGHT	199 LBS
AVERAGE JOINT LENGTH	31 FT
PIPE GRADE	N-80
WALL	0.217"
DRIFT	2.347"
PIPE CONNECTION	HYDRIL 511
BOX OD	2.875"
PIN OD	2.875"
NEW PIPE MINIMUM PARTING LOAD	100,000 LBS
NEW PIPE TORSIONAL	8,600 FT-LBS
NEW PIPE BURST	10,570 PSI
NEW PIPE COLLAPSE	11,170 PSI
CONNECTION MINIMUM PARTING LOAD	100,000 LBS
CAPACITY	0.00597 BBL/FT
DISPLACEMENT	0.00236 BBL/FT
CONNECTION PRESSURE RATING, BURST	10,506 PSI
CONNECTION PRESSURE RATING, COLLAPSE	AS PER NEW PIPE
CONNECTION TORSIONAL YIELD	2,800 FT-LBS
CONNECTION MAKE-UP MINIMUM	700 FT-LBS
CONNECTION MAKE-UP TARGET	800 FT-LBS

Note: All used figures have **NO** safety factor included for tension, temperature, or general S.F. etc.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 03/08/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Mourre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------