

SPECIFICATION SHEET

2 7/8" P-110, 7.90 LBS/FT, HYDRIL 533 TUBING

PIPE OD / ID	2.875" / 2.323"
PIPE WEIGHT	7.90 LBS/FT
AVERAGE JOINT WEIGHT	245 LBS
AVERAGE JOINT LENGTH	31 FT
PIPE GRADE	P-110
WALL	0.276"
DRIFT	2.229" MIN
PIPE CONNECTION	HYDRIL 533
BOX OD	3 9/32"
PIN OD	3 3/16"
NEW PIPE TENSILE (YIELD)	248,000 LBS
NEW PIPE TORSIONAL	14,200 FT-LBS
NEW PIPE BURST	18,480 PSI
NEW PIPE COLLAPSE	19,090 PSI
CONNECTION TORQUE YIELD	9,100 FT-LBS
CONNECTION PRESSURE RATING, BURST	AS PER NEW PIPE
CONNECTION PRESSURE RATING, COLLAPSE	AS PER NEW PIPE
CONNECTION MAKE-UP MINIMUM	2,400 FT-LBS
CONNECTION MAKE-UP TARGET	2,800 FT-LBS

Note: All used figures have **NO** safety factor included for tension, temperature, or general S.F. etc.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 03/08/07	Approved by: Colin Cooper	Date: 06/08/07	Approved by: Darren Murre	Date: 10/08/07
------------------------------	-------------------	------------------------------	-------------------	------------------------------	-------------------