

SPECIFICATION SHEET

3 1/2" OD, NC38, 4 3/4" X 2 1/4" TJ, HEAVY WEIGHT - CONVENTIONAL

PIPE OD	3 1/2"
ADJUSTED WEIGHT	23.29 LBS/FT
AVERAGE WEIGHT (TOTAL LENGTH)	722 LBS/JT
AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	0.625"
AVERAGE INSIDE DIAMETER (NEW)	2.250"
PIPE COLLAPSE RESISTANCE (NEW)	32,270 PSI
PIPE INTERNAL YIELD PRESSURE (NEW)	34,375 PSI
PIPE TENSILE YIELD (NEW)	621,000 LBS
PIPE TORSIONAL YIELD (NEW)	36,900 FT-LBS
CONNECTION	NC38
PIN / BOX OD	4.750"
PIN / BOX ID	2.250"
HARDBANDING	ARMACOR M
TOOL JOINT TENSILE YIELD (NEW)	725,000 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	17,600 FT-LBS
PIN / BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	8,800 FT-LBS
MAKE UP TORQUE (MAXIMUM)	10,500 FT-LBS
FLUID DISPLACEMENT	0.356 GAL/FT
FLUID CAPACITY	0.207 GAL/FT
DRIFT SIZE	2.125"

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 10,500 ft-lbs

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 10/08/07	Approved by: Colin Cooper	Date: 21/08/07	Approved by: Darren Mourre	Date: 17/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------