

SPECIFICATION SHEET

4" OD, XT39, 4 7/8" X 2 9/16" TJ, HEAVYWEIGHT – TRI-SPIRAL

PIPE OD	4"
ADJUSTED WEIGHT	29.82 LBS/FT
AVERAGE WEIGHT (TOTAL LENGTH)	925 LBS/JT
AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	0.719"
AVERAGE INSIDE DIAMETER (NEW)	2.562"
PIPE COLLAPSE RESISTANCE (NEW)	32,437 PSI
PIPE INTERNAL YIELD PRESSURE (NEW)	34,602 PSI
PIPE TENSILE YIELD (NEW)	815,200 LBS
PIPE TORSIONAL YIELD (NEW)	55,300 FT-LBS
CONNECTION	XT39
PIN / BOX OD	4.875"
PIN / BOX ID	2.562"
HARDBANDING	ARMACOR M
TOOL JOINT TENSILE YIELD (NEW)	668,600 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	33,900 FT-LBS
PIN / BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	11,400 FT-LBS
MAKE UP TORQUE (MAXIMUM)	20,300 FT-LBS
FLUID DISPLACEMENT	0.456 GAL/FT
FLUID CAPACITY	0.268 GAL/FT
DRIFT SIZE	2.438"

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 20,300 ft-lbs

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 10/08/07	Approved by: Colin Cooper	Date: 21/08/07	Approved by: Darren Murre	Date: 17/08/07
------------------------------	-------------------	------------------------------	-------------------	------------------------------	-------------------