

SPECIFICATION SHEET

4" OD, XT-M39, 5" X 2 9/16" TJ, HEAVYWEIGHT - CONVENTIONAL

| | |
|--------------------------------------|---------------|
| PIPE OD | 4" |
| ADJUSTED WEIGHT | 28.69 LBS/FT |
| ACTUAL AVERAGE WEIGHT (TOTAL LENGTH) | 889 LBS/JT |
| ACTUAL AVERAGE LENGTH | 31.00 FT |
| NOMINAL WALL THICKNESS (NEW) | 0.719" |
| AVERAGE INSIDE DIAMETER (NEW) | 2.562" |
| PIPE COLLAPSE RESISTANCE (NEW) | 32,437 PSI |
| PIPE INTERNAL YIELD PRESSURE (NEW) | 34,602 PSI |
| PIPE TENSILE YIELD (NEW) | 815,200 LBS |
| PIPE TORSIONAL YIELD (NEW) | 55,300 FT-LBS |
| CONNECTION | XT-M39 |
| PIN / BOX OD | 5.000" |
| PIN / BOX ID | 2.562" |
| HARDBANDING | ARMACOR M |
| TOOL JOINT TENSILE YIELD (NEW) | 668,900 LBS |
| TOOL JOINT TORSIONAL YIELD (NEW) | 34,100 FT-LBS |
| PIN / BOX LENGTH | 24" / 24" |
| MAKE UP TORQUE (MINIMUM) | 17,000 FT-LBS |
| MAKE UP TORQUE (MAXIMUM) | 20,400 FT-LBS |
| FLUID DISPLACEMENT | 0.438 GAL/FT |
| FLUID CAPACITY | 0.268 GAL/FT |
| DRIFT SIZE | 2.437" |

Note: Connections should be made up to maximum make-up torque value to ensure the integrity of the gas tight seal.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

| | | | | | |
|------------------------------|-------------------|------------------------------|-------------------|------------------------------|-------------------|
| Originator: Doug Farquhar | Date: 10/08/07 | Approved by: Colin Cooper | Date: 21/08/07 | Approved by: Darren Murre | Date: 17/08/07 |
|------------------------------|-------------------|------------------------------|-------------------|------------------------------|-------------------|