

SPECIFICATION SHEET

5 1/2" OD, HT55, 7 1/4" X 3 1/4" TJ, HEAVY WEIGHT - CONVENTIONAL

PIPE OD	5 1/2"
ADJUSTED WEIGHT	60.87 LBS/FT
ACTUAL AVERAGE WEIGHT (TOTAL LENGTH)	1,887 LBS/JT
ACTUAL AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	1.125"
AVERAGE INSIDE DIAMETER (NEW)	3.250"
PIPE COLLAPSE RESISTANCE (NEW)	35,795 PSI
PIPE INTERNAL YIELD PRESSURE (NEW)	39,375 PSI
PIPE TENSILE YIELD (NEW)	1,700,900 LBS
PIPE TORSIONAL YIELD (NEW)	151,700 FT-LBS
CONNECTION	HT55
PIN / BOX OD	7.250"
PIN / BOX ID	3.250"
HARDBANDING	ARMACOR 'M'
TOOL JOINT TENSILE YIELD (NEW)	1,630,100 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	105,500 LBS-FT
PIN / BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	41,600 FT-LBS
MAKE UP TORQUE (MAXIMUM)	63,500 FT-LBS
FLUID DISPLACEMENT	0.930 GAL/FT
FLUID CAPACITY	0.431 GAL/FT
DRIFT SIZE	3.125"

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 63,500 ft-lbs

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 10/08/07	Approved by: Colin Cooper	Date: 21/08/07	Approved by: Darren Murre	Date: 17/08/07
------------------------------	-------------------	------------------------------	-------------------	------------------------------	-------------------