

## SPECIFICATION SHEET

5" OD, XT50, 6 5/8" X 3" TJ, HEAVY WEIGHT - CONVENTIONAL

PIPE OD	5"
ADJUSTED WEIGHT	49.77 LBS/FT
AVERAGE WEIGHT (TOTAL LENGTH)	1,543 LBS/JT
AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	1.000"
AVERAGE INSIDE DIAMETER (NEW) TUBE	3.000"
PIPE COLLAPSE RESISTANCE (NEW)	17,600 PSI
PIPE INTERNAL YIELD PRESSURE (NEW)	19,250 PSI
PIPE TENSILE YIELD (NEW)	691,200 LBS
PIPE TORSIONAL YIELD (NEW)	56,500 FT-LBS
CONNECTION	XT50
PIN/BOX OD	6.625"
PIN ID, BOX ID	3.000"
HARDBAND	ARMACOR M
TOOL JOINT TENSILE YIELD (NEW)	1,562,600 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	105,300 FT-LBS
PIN & BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	35,100 FT-LBS
MAKE UP TORQUE (MAXIMUM)	63,200 FT-LBS
FLUID DISPLACEMENT	0.760 GAL/FT
FLUID CAPACITY	0.367 GAL/FT
DRIFT SIZE	2.875"

**Note:** Make up torque should always be higher than anticipated drilling torque – to a maximum of 63,200 ft-lbs

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 10/08/07	Approved by: Colin Cooper	Date: 21/08/07	Approved by: Darren Murre	Date: 17/08/07
------------------------------	-------------------	------------------------------	-------------------	------------------------------	-------------------