

SPECIFICATION SHEET

5" OD, XT50, 6.5" X 3" TJ, HEAVY WEIGHT - TRI-SPIRAL

PIPE OD	5"
ADJUSTED WEIGHT	51.11 LBS/FT
AVERAGE WEIGHT (TOTAL LENGTH)	1,585 LBS/JT
AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	1.000"
AVERAGE INSIDE DIAMETER (NEW)	3.000"
PIPE COLLAPSE RESISTANCE (NEW)	17,600 PSI
PIPE BURST RESISTANCE (NEW)	19,250 PSI
PIPE TENSILE YIELD (NEW)	691,200 LBS
PIPE TORSIONAL YIELD (NEW)	56,500 FT-LBS
CONNECTION	XT50
PIN / BOX OD	6.500"
PIN / BOX ID	3.000"
HARDBANDING	ARMACOR M
TOOL JOINT TENSILE YIELD (NEW)	1,562,600 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	98,300 LBS-FT
PIN / BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	31,000 FT-LBS
MAKE UP TORQUE (MAXIMUM)	59,000 FT-LBS
FLUID DISPLACEMENT	0.781 GAL/FT
FLUID CAPACITY	0.367 GAL/FT
DRIFT SIZE	2.688"

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 59,000 ft-lbs.

Originator: Doug Farquhar	Date: 12/03/07	Approved by: Colin Cooper	Date: 13/03/07	Approved by: R O'Neil	Date: 13/03/07
------------------------------	-------------------	------------------------------	-------------------	--------------------------	-------------------

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.