

## SPECIFICATION SHEET

### 6 5/8" FH, 8 1/2" X 4 1/2" TJ, HEAVY WEIGHT - CONVENTIONAL

PIPE OD	6 5/8"
ADJUSTED WEIGHT	75.02 LBS/FT
ACTUAL AVERAGE WEIGHT (TOTAL LENGTH)	2,326 LBS/JT
ACTUAL AVERAGE LENGTH	31.00 FT
NOMINAL WALL THICKNESS (NEW)	1.063"
AVERAGE INSIDE DIAMETER (NEW) TUBE	4.499"
PIPE COLLAPSE RESISTANCE (NEW)	26,942 PSI
PIPE INTERNAL YIELD PRESSURE (NEW)	28,079 PSI
PIPE TENSILE YIELD (NEW)	1,857,400 LBS
PIPE TORSIONAL YIELD (NEW)	216,100 FT-LBS
CONNECTION	6 5/8" FH
PIN/BOX OD	8.500"
PIN ID, BOX ID	4.500"
HARDBAND	ARMACOR M
TOOL JOINT TENSILE YIELD (NEW)	1,580,100 LBS
TOOL JOINT TORSIONAL YIELD (NEW)	82,000 LBS-FT
PIN & BOX LENGTH	24" / 24"
MAKE UP TORQUE (MINIMUM)	41,000 FT-LBS
MAKE UP TORQUE (MAXIMUM)	42,100 FT-LBS
FLUID DISPLACEMENT	1.148 GAL/FT
FLUID CAPACITY	0.826 GAL/FT
DRIFT SIZE	4.250"

**Note:** Make up torque should always be higher than anticipated drilling torque – to a maximum of 42,100 ft-lbs.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

Originator: Doug Farquhar	Date: 10/08/07	Approved by: Colin Cooper	Date: 21/08/07	Approved by: Darren Mourre	Date: 17/08/07
------------------------------	-------------------	------------------------------	-------------------	-------------------------------	-------------------