

SPECIFICATION SHEET

6 5/8" OD, FH, 8" X 5" TJ, HEAVY WEIGHT - SPIRAL

| | |
|--------------------------------------|----------------|
| PIPE OD | 6 5/8" |
| ADJUSTED WEIGHT | 70.37 LBS/FT |
| ACTUAL AVERAGE WEIGHT (TOTAL LENGTH) | 2,182 LBS/JT |
| ACTUAL AVERAGE LENGTH | 31.00 FT |
| NOMINAL WALL THICKNESS (NEW) | 1.063" |
| AVERAGE INSIDE DIAMETER (NEW) TUBE | 4.500" |
| PIPE COLLAPSE RESISTANCE (NEW) | 14,812 PSI |
| PIPE INTERNAL YIELD PRESSURE (NEW) | 15,436 PSI |
| PIPE TENSILE YIELD (NEW) | 1,021,200 LBS |
| PIPE TORSIONAL YIELD (NEW) | 118,800 FT-LBS |
| CONNECTION | 6 5/8" FH |
| PIN/BOX OD | 8.000" |
| PIN ID, BOX ID | 5.000" |
| HARDBAND | ARNCO 200 XT |
| TOOL JOINT TENSILE YIELD (NEW) | 1,896,100 LBS |
| TOOL JOINT TORSIONAL YIELD (NEW) | 88,000 LBS-FT |
| PIN & BOX LENGTH | 24" / 24" |
| MAKE UP TORQUE (MINIMUM) | 43,900 FT-LBS |
| MAKE UP TORQUE (MAXIMUM) | 50,500 FT-LBS |
| FLUID DISPLACEMENT | 1.075 GAL/FT |
| FLUID CAPACITY | 0.826 GAL/FT |
| DRIFT SIZE | 4.875" |

Note: Make up torque should always be higher than anticipated drilling torque – to a maximum of 50,500 ft-lbs.

The information on this specification sheet is provided for illustration purposes only and has been extracted from information available from the manufacturer and other public domain sources. Premier Oilfield Rentals Ltd accepts no responsibility or liability to any party for the accuracy of the technical information provided or for any error, omission or misstatement. The reader is fully expected to make independent enquiry and to rely on their own skill and judgement in evaluating whether any particular equipment is suitable.

| | | | | | |
|------------------------------|-------------------|------------------------------|-------------------|------------------------------|-------------------|
| Originator: Doug Farquhar | Date: 10/08/07 | Approved by: Colin Cooper | Date: 21/08/07 | Approved by: Darren Murre | Date: 17/08/07 |
|------------------------------|-------------------|------------------------------|-------------------|------------------------------|-------------------|